

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4000</b>				
Compressor	51-16250A	AR92109	1975 & above	A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343	1975 & above	A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343	1975 & above	A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>4020</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>4030</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4040</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49619		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4050</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4050</b>				
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4055</b>				
Compressor	CO-1005CA	TY6626	006592 & below	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4230</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4240</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49619		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4250</b>				
Compressor	CO-1005CA	TY6626	006592 & below	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4255</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4320</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port

<b>4430</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

<b>4440</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49619		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

<b>4450</b>				
Compressor	CO-1005CA	TY6626	006592 & below	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

<b>4455</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

- 1: Check illustrations
- 2: May require oil change
- 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4520</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port

<b>4555</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

<b>4560</b>				
Compressor	CO-1005CA	TY6626	sn -> 3583	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Compressor	CO-1024CA	TY6784	sn 3584 ->	Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Clutch	600-1300	RE10975	sn -> 3583	Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

<b>4620</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port

<b>4630</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5070			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

- 1: Check illustrations
- 2: May require oil change
- 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4640</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5075			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4650</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4755</b>				
Compressor	CO-1005CA	TY6626	sn -> 10878	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Compressor	CO-1024CA	TY6784	sn 10879 ->	Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4760</b>				
Compressor	CO-1005CA	TY6626	sn -> 3365	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Compressor	CO-1024CA	TY6784	sn 3366 ->	Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Clutch	600-1300	RE10975	sn -> 3365	Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4840</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor Conv.	AC-9-5075			Kit Converts A6 to Sanden: compressor, mtg brackets, hoses, pressure switch, hardware
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>4850</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4955</b>				
Compressor	CO-1005CA	TY6626	sn - > 10370	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Compressor	CO-1024CA	TY6784	sn 10371 - >	Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Clutch	600-1300	RE10975	sn - > 10370	Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>4960</b>				
Compressor	CO-1005CA	TY6626	sn - > 5729	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Compressor	CO-1024CA	TY6784	sn 5730 - >	Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Clutch	600-1300	RE10975	sn - > 5729	Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>5020</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>6030</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>6200</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>6200</b>				
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6200L</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6300</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6300L</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6400</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6400L</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6500</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>6500L</b>				
Compressor	TBA_AL78779	AL78779		Nippondenso reman with clutch
Clutch	TBA_AL78494	AL78494		Nippondenso new
Expansion Valve	TBA_AL77579	AL77579, RE62		Block type
Receiver Dryer	TBA_AL77581	AL77581		
<b>7020</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>7020</b>				
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>7200</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	TBA_AL77579	AL77579, RE62	tsn -> 3822	Block type
Expansion Valve	904-1860	RE57575, RE17	tsn 3823 ->	Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7210</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7400</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	TBA_AL77579	AL77579, RE62	tsn -> 5043	Block type
Expansion Valve	904-1860	RE57575, RE17	tsn 5043 ->	Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7410</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7510</b>				
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
<b>7520</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-244	AR49961		Flare Inlet 3/8 M, Outlet 1/2 M, 8" capillary 3/8" tube, 1-1/2 ton, internally equalized
Receiver Dryer	804-260	AR45867		3.00 x 5.25, male flare Inlet 3/8 MF x Outlet 3/8 MF, sight glass top, switch port
<b>7600</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	TBA_AL77579	AL77579, RE62	tsn -> 8003	Block type
Expansion Valve	904-1860	RE57575, RE17	tsn 8004 ->	Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4

- 1: Check illustrations
- 2: May require oil change
- 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>7600</b>				
Receiver Dryer	7-9111-APC	RE46169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7610</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7700</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	TBA_AL77579	AL77579, RE62	tsn - > 10007	Block type
Expansion Valve	904-1860	RE57575, RE17	tsn 10008 - >	Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE46169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7710</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7800</b>				
Compressor	1 902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	TBA_AL77579	AL77579, RE62	tsn - > 15007	Block type
Expansion Valve	904-1860	RE57575, RE17	tsn 15008 - >	Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE46169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>7810</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575, RE17		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8100</b>				
Compressor	1 902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8110</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8200</b>				
Compressor	1 902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>8200</b>				
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8210</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8210T</b>				
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8300</b>				
Compressor	1 902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8310</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8310T</b>				
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8400</b>				
Compressor	1 902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8410</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134
<b>8410T</b>				
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	804-1890	AT162848		4.00 x 8.95, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, Sight glass side, R12/R134

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>8430</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8440</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8450</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8560</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE24620		Accumulator
<b>8570</b>				
Compressor	CO-1024CA	TY6784		Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE51918		Accumulator
<b>8630</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>8640</b>				
Compressor	51-16250A	AR92109		A6 new with clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS, mineral oil [repl 1131250L]
Compressor	50-037	AR77343		A6 reman with new clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Compressor	50-014	AR77343		A6 reman with reman clutch 5.62 dia, 1 grv, 12v, 10:00 coil, SHS head
Clutch	600-258	AR71287		A6 new, no coil 5.62 dia, 1 grv (coil separate 600-400)
Clutch	600-423	AR71287		A6 reman, no coil (use 600-258) 5.62 dia, 1 grv (coil separate 600-400)
Expansion Valve	904-304	AH140818		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8650</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8760</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE24620		Accumulator
<b>8770</b>				
Compressor	CO-1024CA	TY6784		Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE51918		Accumulator
<b>8850</b>				
Compressor	CO-1005CA	TY6626	2708 & below	Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	904-304	AR58482		Oring Inlet 3/8 M, Outlet 1/2 M, 12" capillary 3/8" coil, 2 ton, ext. equalizer 13" x 1/4FO
Receiver Dryer	7-9111-APC	AR74486		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>8870</b>				
Compressor	CO-1024CA	TY6784		Nippondenso new with clutch 5.748 pulley, 1 grv, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE51918		Accumulator
<b>8960</b>				
Compressor	CO-1005CA	TY6626		Nippondenso new with clutch 5.75 dia, ear mount, 6E171 Model
Clutch	600-1300	RE10975		Nippondenso new 5.75 dia, 1 grv
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE24620		Accumulator
<b>8970</b>				
Expansion Valve	440-475	RE51969		Orifice tube type
Receiver Dryer	804-556	RE51918		Accumulator

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration

# John Deere Tractor



Description	EPP	OEM	S/N note	Part Notes
<b>9100</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9120</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169	tsn -> 11461	4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9200</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9220</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169	tsn -> 11461	4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9300</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9320</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169	tsn -> 11461	4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9400</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169		4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9420</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169	tsn -> 11461	4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass
<b>9520</b>				
Compressor	902-209	TY6764		Nippondenso reman with clutch 5.748 pulley, 8 PV, 12V, R134a; 10PA17C [no charge ports]
Expansion Valve	904-1860	RE57575		Block, oring Inlet 3/8 Outlet 1/2, Suction: in 5/8, out 3/4
Receiver Dryer	7-9111-APC	RE49169	tsn -> 11461	4.00 x 7.90, male/female oring Inlet 3/8 FO x Outlet 3/8 MO, (2) Sight glass

1: Check illustrations  
 2: May require oil change  
 3: New, check illustration